

KB100 EQ Wired Full Size Keyboard

Part Number: K63727DE, EAN Code: 5028252640077 | Part Number: K63727ES, EAN Code: 5028252640091 Part Number: K63727FR, EAN Code: 5028252640084 | Part Number: K63727GK, EAN Code: 5028252650076 Part Number: K63727IT, EAN Code: 5028252640107 | Part Number: K63727PN, EAN Code: 5028252645249 Part Number: K63727UK, EAN Code: 5028252640060 | Part Number: K63727WW, EAN Code: 5028252646086

Simple and more sustainable.

Designed with sustainability in mind, the KB100 EQ Wired Full Size Keyboard is a reliable, value-for-money solution ideal for large office deployments.

Made using 65% post-consumer recycled (PCR) material in the outer case and keycaps, KB100 features a spill-proof design. Its sealed membrane resists coffee, water and other liquids and protects the keyboard electronics from unexpected mishaps.

Supporting comfort and productivity, the keyboard is also an ideal choice for the touch typist. It offers an ISO full-size layout with responsive tactile keys for all-day comfort, together with a numeric keypad to support productivity. The wired USB-A connection provides a convenient and reliable experience.

- Outer case and keycaps composed of 65% post-consumer recycled (PCR) content
- Full size ISO layout
- Tactile keys provide a comfortable typing experience
- Sealed membrane design protects the keyboard against accidental spills
- Wired USB-A connection eliminates need for batteries
- · Plug-and-play with Windows and macOS
- Wipe down protection meets MIL-STD-810H Method 504.3
- 3-year limited warranty



Kensington

KB100 EQ Wired Full Size Keyboard

Part Number: K63727DE, EAN Code: 5028252640077 | Part Number: K63727ES, EAN Code: 5028252640091 Part Number: K63727FR, EAN Code: 5028252640084 | Part Number: K63727GK, EAN Code: 5028252650076 Part Number: K63727IT, EAN Code: 5028252640107 | Part Number: K63727PN, EAN Code: 5028252645249 Part Number: K63727UK, EAN Code: 5028252640060 | Part Number: K63727WW, EAN Code: 5028252646086



Sustainability Focused

Aimed at reducing our environmental impact, the outer case and keycaps are composed of 65% post-consumer recycled (PCR) content.



Full Size Keyboard

Designed to maximise productivity, the ISO layout is organized into 6 rows with a numeric keypad.



Tactile Keys

Ideal for the touch typist, responsive tactile keys support improved typing accuracy, increasing typing speed and reducing fatigue.



Spill-Proof Design

A sealed membrane ensures that any spills of water, coffee or other liquids will not damage the electronics and can be simply wiped dry.



Wired USB-A Connection

The wired USB-A cable provides a reliable plug-and-play connection. Windows and macOS compatible.



Wipe Down Protection

Meets MIL-STD-810H Method 504.3 Contamination by Fluids with disinfectants with no degradation.*

* No visual degradation or inability to use as directed upon test completion.



KB100 EQ Wired Full Size Keyboard

Part Number: K63727DE, EAN Code: 5028252640077 | Part Number: K63727ES, EAN Code: 5028252640091 | Part Number: K63727FR, EAN Code: 5028252640084 | Part Number: K63727GK, EAN Code: 5028252650076 | Part Number: K63727IT, EAN Code: 5028252640107 | Part Number: K63727PN, EAN Code: 5028252645249 | Part Number: K63727UK, EAN Code: 5028252640060 | Part Number: K63727WW, EAN Code: 5028252646086

System		

System Requirement		
	System Resource Requirement	1 x USB-A
	Operating Systems Supported	Windows 7 or above, macOS 10.14 or above
Product Dimensions		
	Product Unit Dimensions	444.7 x 147.4 x 34.7mm (17.51 x 5.80 x 1.37"
	Keyboard Unit Weight	511g (1.13lbs)
	Keyboard Colour	Black
Packaging Dimensions		
	Packaging Style	Brown box, FSC™ certified
	Packaging Dimensions (unit)	171 x 486 x 32mm (6.73 x 19.11 x 1.26")
	Packaging Dimensions (carton)	187 x 475 x 196mm (7.36 x 18.7 x 7.72")
	Packaging Weight (unit)	0.65kg (1.43lbs)
	Packaging Weight (master carton)	3.7kg (8.14lbs)
	Master Carton	5pcs
	Packaging Content	Keyboard Warranty card Compliance sheet
Power & Environmental		
	Operating Temperature	0 to 40°C (32 to 104°F)
	Storage Temperature	-18 to 60°C (-0.4 to 140°F)
	Relative Humidity	0% to 85% non-condensing
Country of Origin, Regula	tory and Warranty	
	Country of Origin	China
	Warranty	3-year Limited
	Certifications & Compliance	CE, FCC, UKCA, IC, RCM



